# **CAMBRO**

## Camshelving® Elements Series

# Stationary Starter & Add-On Units 4 Solid or 4 Vented and Solid Shelves

(3 Vented + 1 Solid)

HEIGHT	DEPTHS	LENGTHS	
1	3	8	
64"	18" 21"	24" 48" 30" 54"	
	24"	36" 60" 42" 72"	

#### • Starter Units include:

2 factory assembled post kits, 8 stationary shelf traverses, stationary traverse dovetails and shelf plates.

#### Add-On Units include:

1 factory assembled post kit, 8 stationary shelf traverses, stationary traverse dovetails and shelf plates.

All units ship complete in 1 box.





#### **Features & Benefits**

- Designed to easily support the performance demands of a busy foodservice operation with medium to heavy storage needs.
- Use in walk-in coolers, freezers, dry storage, warewashing areas, loading docks or front of the house. Withstands storage temperatures -36° to 190°F (-38° to 88°C). Impervious to moisture, chemicals, salt, food acids and humidity.
- Install solid shelf on bottom to prevent water/cleaning liquid from sloshing onto products. Install on top to protect product on lower shelves from cooler condensation.
- Posts and traverses are made of a revolutionary, extremely strong composite material. Stronger than common wire shelving and lighter in weight than Camshelving Premium Series. Traverse dovetails attach easily to secure shelf traverses.
- Smooth polypropylene shelf plates contain Camguard, an antimicrobial technology that inhibits the growth of mold, fungus and bacteria that may cause odors, stains and product degradation.
- Shelving Units interconnect in straight lines with shared posts.
   Uniquely engineered Post Connectors offer exceptional cross stabilization.
   No add-on clips or "S" hooks required.
- Use corner connectors to add shelves in corners or to install intermediate shelves between 2 starter units to maximize space
- Posts and traverses wipe clean. Traverses and shelf plates remove easily for cleaning.
- Shelf traverses can be removed and adjusted at 4" (10,2 cm) increments.
- Sturdy reinforced nylon foot adjusts easily to level units.
- Requires some assembly with minimal parts. Use a rubber mallet only.

Printed in USA. REV. 12/16

- Lifetime warranty against rust and corrosion (posts, traverses and shelf plates).
- Available in 1 color Brushed Graphite (580).

Item No			
Quantity _			
AIA File / S	pec No		
loh			




**Stationary Starter Unit** 

Stationary Add-On Unit

## 4 Shelf Unit Weight Bearing Chart

Single Unit Single Unit with Dunnage Stand Corner Unit with 2 Dunnage Stands



3200 lbs.

Maximum
Unit Capacity

2800 lbs. Maximum Unit Capacity 1800 lbs.

Maximum
Unit Capacity

\* Dunnage Stands add stability and increase weight bearing capacity on bottom shelf only. Add to any shelf length. Highly recommended for Starter Units 54" and longer, all Corner Units, U-Shape Units and units specified for heavier loads.

### **Approvals**



Post Connectors, Corner Connectors, Seismic Foot, Wall Fastener, Identification Tags, Single Shelf Security Cage, Tray Slide Rack, and Shelf Divider Bars are not NSF listed.



# Camshelving® Elements Series

### Stationary Starter & Add-On Units 4 Solid or 4 Vented and Solid Shelves

(3 Vented + 1 Solid)

### 4-Shelf Solid Units

**HEIGHT** 





CODE

EA182464S4

EA183064S4

EA183664S4

EA184264S4

EA184864S4

EA185464S4

EA186064S4

EA187264S4

EA212464S4

EA213064S4

EA213664S4

EA214264S4

EA214864S4

LENGTH

22"

28"

34"

40"

46"

52"

58"

70"

22"

28"

34"

40"

46"

Add-On

**DEPTH** 

CODE
ESU182464S4
ESU183064S4
ESU183664S4
ESU184264S4
ESU184864S4
ESU185464S4
ESU186064S4
ESU187264S4

2	1	II	
DE	- Р1	ſΗ	

24"	ESU212464S4
30"	ESU213064S4
36"	ESU213664S4
42"	ESU214264S4
48"	ESU214864S4
54"	ESU215464S4
60"	ESU216064S4
72"	ESU217264S4



54"	ESU215464S4	52"	EA215464S4
60"	ESU216064S4	58"	EA216064S4
72"	ESU217264S4	70"	EA217264S4
24"	ESU242464S4	22"	EA242464S4
30"	ESU243064S4	28"	EA243064S4
36"	ESU243664S4	34"	EA243664S4
42"	ESU244264S4	40"	EA244264S4
48"	ESU244864S4	46"	EA244864S4
54"	ESU245464S4	52"	EA245464S4
60"	ESU246064S4	58"	EA246064S4
72"	ESU247264S4	70"	EA247264S4
Color: Br	ushed Graphite (580).		

**Optional Accessories** 

- Corner Connector Sets
- ☐ Bottom Shelf Dunnage Stands (Low or Tall)
- ☐ Shelf Identification Tags
- Wall Fastener
- □ Seismic Foot
- ☐ Shelf Divider Panel
- Shelf Divider Bars (Straight or Angled)
- ☐ Tray Sliding Rack

Printed in USA. REV. 12/16

- ☐ Single Shelf Security Cage
- ☐ Shelf Traverses (Single or Double)
- □ Drying and Storage Cradles

Quantity AIA File / Spec No.

Add-On

# VS4

### 4-Shelf Units (3 Vented + 1 Solid)

Starter





LENGTH	CODE	LENGTH	CODE
24"	ESU182464VS4	22"	EA182464VS4
30"	ESU183064VS4	28"	EA183064VS4
36"	ESU183664VS4	34"	EA183664VS4
42"	ESU184264VS4	40"	EA184264VS4
48"	ESU184864VS4	46"	EA184864VS4
54"	ESU185464VS4	52"	EA185464VS4
60"	ESU186064VS4	58"	EA186064VS4
72"	ESU187264VS4	70"	EA187264VS4
24"	ESU212464VS4	22"	EA212464VS4
30"	ESU213064VS4	28"	EA213064VS4
36"	ESU213664VS4	34"	EA213664VS4
42"	ESU214264VS4	40"	EA214264VS4
48"	ESU214864VS4	46"	EA214864VS4
54"	ESU215464VS4	52"	EA215464VS4
60"	ESU216064VS4	58"	EA216064VS4
72"	ESU217264VS4	70"	EA217264VS4
24"	ESU242464VS4	22"	EA242464VS4
30"	ESU243064VS4	28"	EA243064VS4
36"	ESU243664VS4	34"	EA243664VS4
42"	ESU244264VS4	40"	EA244264VS4
48"	ESU244864VS4	46"	EA244864VS4
54"	ESU245464VS4	52"	EA245464VS4
60"	ESU246064VS4	58"	EA246064VS4
72"	ESU247264VS4	70"	EA247264VS4

### **Architect Specs**

Posts and Traverses: Proprietary non-corrosive composite material.

Post Connectors: Reinforced nylon.

Shelf Plates: Reinforced polypropylene with Camguard® antimicrobial.

Corner Connectors: Reinforced nylon. Adjustable Foot: Reinforced nylon.

Traverse Dovetails: Reinforced nylon.

Post Connector Wedges: Reinforced polypropylene.

### **Approvals**



Post Connectors, Corner Connectors, Seismic Foot, Wall Fastener, Identification Tags, Single Shelf Security Cage, Tray Slide Rack, and Shelf Divider Bars are not NSF listed.

